Service Call: +86-13711988687



Touch screen single disc metallographic sample grinding and polishing machine

Model: MP-1T

1. Product overview:

iqualitrol MP-1T metallographic sample grinding and polishing machine adopts a high-end touch screen, which can make the speed of the grinding and polishing disc infinitely adjustable in the range 50-1000r/min.

The grinding and polishing process of the sample can be completed by replacing the metallographic sandpaper and polishing fabric.

The shell adopts integral blister, novel appearance, stable rotation, low noise, convenient operation, high working efficiency, and comes with a cooling device, which can cool the sample during grinding and polishing to prevent damage due to overheating of the sample Microstructure.



2. Main functions and features:

- 1. The shell is made of high-end ABS, which has a novel appearance and high-end atmosphere.
- 2. The faucet adopts all-copper chromium plating process, which has good corrosion resistance
- 3. With automatic cleaning function, it can automatically clean the sewage tank to keep the sewage tank clean (optional)
 - 4. Brushless DC motor, stable rotation, low noise, long life (optional)
 - 5. Stepless speed regulation plus eight-speed fixed speed, convenient and quick to meet various needs
- 6. Countdown function, the time can be set arbitrarily, and the machine will stop when the time comes. (Optional)
 - 7. The grinding and polishing plate can be rotated clockwise or counterclockwise to meet different needs

Service Call: +86-13711988687



3. Technical parameters:

Diameter of Grinding Disc	Standard ф203mm (other specifications customized)	
Rotating Speed of Grinding Disc	50-1000r/min, Stepless speed	
Rotating Speed of Grinding Disc	Eight gear fixed speed	
Rotation direction	clockwise and anticlockwise rotation	
power supply	Voltage: 220V Frequency: 50HZ	
Iqualitrol Motor	0.25KW	
Appearance size	730×420×320mm	
weight	35Kg	

4. configuration list:

Product accessories	unit	quantity	Remark
Grinding and polishing disc	рс	1	Installed on the device
Water retaining ring	рс	1	Installed on the device
Pressure ring	рс	1	Installed on the device
Water sandpaper	рс	1	Ф203mm
Polished fabric	рс	1	Ф203mm
Inlet pipe	рс	1	Φ 6 points interface
Outlet pipe	рс	1	Ф32
Technical documents	1 copy of product manual 1 copy of product certificate		